



3RUN
HELM S3
3R137N

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, IDROTECH® WRU grain Nubuck leather thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.
COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN 12568
MIDSOLE flexible antiperforation composite fabric according to EN 12568
SOLE 3 RUN three densities polyurethane antistatic, resistant to hydrolysis ISO 5423-92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**
ANTI TORSION insert in the sole to assure stability on uneven ground
INSOLE MEMORY, three-materials extracomfort with soft latex. Memory no-stress in the heel zone resistant to the body pressure. Perspiring, removable, anatomic, absorbing, antistatic and anti-bacterial

Size 39-47 Shoe weight Sz 42 gr. 560

MATERIALS



TECHNOLOGIES



SECTORS



SOLE



3Run is a line with a **sporty** and youthful character, developed for those who work **indoors** and **outdoors** on **regular surfaces**.
3Run belongs to the **3D generation**. This shoe therefore has **3 different PU injected layers** with relative densities, each specialized to maximize comfort, anti-slip and foot stability.
Some of these models are also equipped with an **antitorsion** insert to guarantee further support to the foot at every step.

PLUS



The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows cleaners, bricklayers) as it increases the stability in the central part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.



3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected.
The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances.
The middle part, with a softer mix, assures comfort when walking.
The higher section, next to the upper, guarantees better stability to the foot.
Three densities and the combination of three colors are the special characteristics of this new shoes generation.

ANTISLIPPING TEST RESULTS

SRC ANTI-SLIPPING SOLE		VERY GOOD
SRA ceramic + NaLS	HEEL >= 0,28 FLAT >= 0,32	0,47 0,47
SRB steel + glycerol	HEEL >= 0,13 FLAT >= 0,18	0,23 0,26